

Sticks 900 - LED module, single sided





Complete LED module for easy and efficient refurbishment of existing Sticks 900 bollards, single sided.

LED type: Citizen Array CALD0414-M8L1

Energy consumption: 8 or 11 W

Operational life: min 50,000 hours at ta max 25°C Colour temperature: 2700 or 3000 K, energy eff. class E

Colour rendering: min 80 Ra Colour accuracy: 3 Steps SDCM

Driver: LED driver, 20 W, dimming optional

Operational life: min 50,000 hours

Exchange of light source:

Demount bollard top by loosening two screws at the bottom. Mount the LED module and connect the cables.

Remount the bollard top.

We include a blank lable in the consignment. Write the old item number on the lable and attach it inside the luminaire.

Variants:

LED modules for Sticks	900, single s	sided						
Item No.	Ligh	Light source						
1923-	8 W 0	8 W Citizen Array, 500 mA						
1924-	11 W	11 W Citizen Array, 700 mA						
	Select colour temperature and other options in the table below.							
Combine with:	Colour temperature		Dimming		Classi	Classification		
	827	2700 K, 80 Ra	empty	without dimming	empty	class II		
	830	3000 K, 80 Ra	٧	1-10 V	J	class I		
			D	Dali				
Example:	1923	1923-830 = single-sided LED module for Sticks 900, 11 W, 3000 K 80 Ra, without dimming						
The above LED module	s fit the follo	wing variants	(X staı	nds for colour cod	e):			
		7234X, 7244X, 7834X, 7844X,						
7840, 7843, 7846, 7848								